

EG 50-S
Ersatz Modul MR16

WATTAGE
6W

LUMEN
600

CRI
>83

UGR
<19

IP20

CE

RoHS

BRIDGELUX
LM80 LED



EG 50-S

Voltage driver	220-240 VAC
Light source	COB
Beam angle	15°/25°/38°/60°
Color temperature	3000K, 4000K
Material	Aluminum
Environment	Indoor
EMC norms	EN55015
Safety norms	EN60598 EN62031 EN61347
Operating temperature	-20°C/+45°C
Expected lifetime	45,000hrs
Weight single package	130g

LED driver

Input voltage	220-240 VAC ~ 50/60Hz
Power factor	>0.90
Output voltage	17.8V
Output current	350mA
Dimmable	Triac
Dimensions	130x42x23mm



Code	EG50-S/15°		EG50-S/38°		EG50-S/60°	
	3000K	4000K	3000K	4000K	3000K	4000K
Current	350mA	350mA	350mA	350mA	350mA	350mA
LED Power	6.3W	6.3W	6.3W	6.3W	6.3W	6.3W
System Power	7.5W	7.5W	7.5W	7.5W	7.5W	7.5W
LED output	785Lm	829Lm	785Lm	829Lm	785Lm	829Lm
Module output	601Lm	632Lm	575Lm	605Lm	605Lm	637Lm
CRI	83	83	83	83	83	83

