

# LED Nord





Paletto per l'illuminazione di giardini e parchi, con effetto di luce discreta. Illuminazione verso il basso a rispetto della normativa contro l'inquinamento luminoso. Design pratico di facile installazione grazie al cavo presa e spina in dotazione il cablaggio è semplice e immediato, possibilità di scelta del palo in 3 diverse misure (da ordinare separatamente).

**Installazione:** a pavimento  
**Corpo:** in alluminio pressofuso UNI EN 1706, verniciato con polvere termoindurente poliesteri  
**Verniciatura:** di tipo poliesteri eseguita a polvere, resistente agli agenti atmosferici e alla corrosione e garantita per 1.000 ore in nebbia salina. Colore Antracite.  
**Diffusore:** in policarbonato opalino infrangibile ed autoestinguente V2, stabilizzato ai raggi UV.  
**Driver:** incorporato  
**Sorgente:** LED **CREE** Fattore di potenza  $\geq 0,90$ . Mantenimento del flusso luminoso al 80%. 50.000h (L80B20)

*Bollard for lighting private gardens or parks, with diffused, discreet and anti-light pollution effect, with a practical design and easy to install thanks to the socket and plug cable provided. The wiring is simple and immediate and the pole comes in 3 different sizes (to be ordered separately).*

**Installation:** floor  
**Body:** in UNI EN 1706 die-cast aluminium, painted with thermohardening polyester powder  
**Painting:** powder polyester coating, resistant to atmospheric agents and corrosion and guaranteed for 1,000 hours in salt spray. Colour: Anthracite.  
**Diffuser:** in V2 self-extinguishing and shatter-proof opal polycarbonate, UV stabilised.  
**Driver:** built-in  
**Source:** CREE LED. Power factor  $\geq 0.90$ . Maintenance of 80% luminous flux. 50.000h (L80B20).



**Norme di riferimento**  
**Standard reference**  
EN60598-1  
EN60598-2-1  
EN62471  
EN62031  
EN60598-2-5  
EN61547

220-240 Vac	50/60 Hz	IP54	IK09	CRI >80	+40 °C -20		850°	
<b>DRIVER INCLUDED</b>								

colour	Ø mm	W	LED	Optic	K	lm	pcs	Kg	CELL
A	180	10	Led SMD	120°	3000	720	1	0,8	25000



**Accessori non inclusi - Not included accessories**

colour	H mm	Descrizione	CELL
A	380	Palo Ø 40mm Pole Ø 40mm	25000/PAL38
A	750		25000/PAL75
A	1100		25000/PAL110

