

Approval Marks



Item		Value	Remark
Input	Nominal voltage	220–240V	
	Nominal frequency	50–60Hz	
	AC voltage range	198–264V	
	DC voltage range (start)	NA	
	DC voltage range (operation)	NA	
	Nominal current		
	G5R15W300LRP	75mA	
	G5R15W350LRP	85mA	
	Total Harmonic Distortion (THD)	< 15%	Full load @230VAC
	Power factor(Displacement factor)	0.85C-0.9C	Full load @230VAC
	Displacement factor	0.85C-0.9C	Full load @230VAC
	Efficiency	85%(Typ.)	Full load @230VAC
	No-load power	NA	
	Stand-by power	NA	
	Protection class	NA	
	Inrush current	9A / 140us	
		Type B , 10A MCB	47
		Type B , 16A MCB	75
	Max.units per circuit breaker	Type C , 10A MCB	59
		Type C , 16A MCB	94
Earth leakage current		NA	
Output	Nominal voltage range		
	G5R15W300LRP	26-43Vdc	
	G5R15W350LRP	26-43Vdc	
	Maximum voltage		
	G5R15W300LRP	50Vdc	
	G5R15W350LRP	50Vdc	
	Nominal current range		Full load @230VAC
	G5R15W300LRP	300mA	
G5R15W350LRP		350mA	

	Item	Value	Remark
Output	Current accuracy	± 5%	Full load @230VAC
	Typical output LF current ripple	± 5%	Low Frequency< 120Hz Full load @230VAC
	Starting time	< 0.5S	Full load @230VAC
	SVM	≤ 0.4	Full load @230VAC
	P _{st} LM	≤ 1	Full load @230VAC
	Nominal power range		
	G5R15W300LRP	7.5-13W	
	G5R15W350LRP	9-15W	
	Maximum power	15W	
Dimming	Dimming control	NA	
	Dimming technique	NA	
	PWM frequency	NA	
	Dimming range	NA	
	Lowest dimming current	NA	
	Galvanic isolation	NA	
Environment	Ambient temperature range t _a	-20°C - +50°C	
	Maximum case temperature t _c	90°C	
	Max. case temp. in fault condition	110°C	
	Storage temperature range	-40°C - +85°C	
	Relative humidity	10% - 95%	
	Surge transient protection	1 kV,2kV	L/N,L-PE/N-PE
	Environmental rating	Indoor	
	IP rating	IP20	
	Mains switching cycles	> 100,000	
	Expected lifetime		
	Output load 7.5-15W	> 50,000 h, t _c 90 °C @ t _a 50 °C	0.2 % / 1,000 h failure rate
	Output load 7.5-15W	> 41,000 h, t _c 90 °C @ t _a 60 °C	0.24 % / 1,000 h failure rate
Packing	Gross weight/box	12.2 kg	
	Net weight/box	11 kg	
	Pcs/box	180 PCS	
	Dimension/box	385(L)*310(W)*260(H)mm	
Protections			
	Short-circuit Protection	Auto recovery	
	Open-circuit Protection	Auto recovery	
	Overload Protection	Auto recovery	
Conformity & Standards			
Safety standard:		EN 61347-1, EN 61347-2-13, EN 62493	
Performance:		EN 62384	
CCC standard:		GB17625.1,GB/T17743,GB19510.1,GB19510.14	
EMC standard:		EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61547	

Cable information




PRI Connection	L	N
Color	Brown	Blue
Wire type	7022	7022
Wire diameter	AWG20	AWG20
Wire length	143mm	143mm
Stripping	6mm	6mm
tolerance	±5mm	±5mm

Sec Connection	+	-
Color	Red	Black
Wire type	3385	3385
Wire diameter	AWG22	AWG22
Wire length	142mm	142mm
Stripping	6mm	6mm
tolerance	±5mm	±5mm


* If not mentioned, all the test conditions are based on full load at 230VAC input (for 220-240 VAC input).

Subject to change without notice, HEP guarantees all products perform functionally well

Electrical Values



Physical Parameter



L : 48 mm M : 46.7 mm N : 43.5 mm

H : 22 mm R : 1.6 mm


Tolerance : +/-1 mm , R : +/-0.5 mm

Housing Material : Polycarbonate / Potting

Soldering : Lead-Free, Comply With RoHS

Label : Surface Print

TC point at bottom side of the case



L : 17.5 mm H : 19.5 mm

Wiring Diagram

