

# DUELUCI... - DOPPEL... - 2BT/PS



Transformateurs électroniques pour deux sources lumineuses

Elektronische Dimmertransformatoren für zwei Lichtquellen

Références - Referenzen	
EN61347-1 (2009)	Sécurité - Sicherheit
EN61058-1	
EN61347-2-2 (2001) + A1 + A2	
EN61047	Performances - Performances
EN61000-3-2 (2007)	Limites harmoniques - Harmonische Grenzwerte
EN 55015 (2008) + A2 (2009)	Emission R.F.I. - R.F.I. Emissionen
EN61547 (2010)	Immunité - Störfestigkeit
EN61000-3-3	Flikers



Point lumineux de signalisation nocturne  
Nachlicht

12V INT. + 230V DIM.

Article Artikel	W min. max.	V	Hz	ta °C	W	L mm	P mm	H mm	Code Art.-Nr.
DUELUCI TD.2 N	35÷50W 12V + 100÷500W 230V	230	50÷60	-15.. +35	Ti	140	83	36	40 RL5766 ●



N - Cod: 60089900  
Boîte à commander à part - Gehäuse muss extra bestellt werden

12V + 230V + 2 POT.

Article Artikel	W min. max.	V	Hz	ta °C	W	L mm	P mm	H mm	Code Art.-Nr.
DOPPEL N	35÷50W 12V + 75÷300W 230V	230	50÷60	-15.. +35	Te	149	140	31	50 RQ5766 ●



12V + 230V + 2 POT.

Article Artikel	W min. max.	V	Hz	ta °C	W	L mm	P mm	H mm	Code Art.-Nr.
DUELUCI TD/PS N	35÷50W 12V + 100÷500W 230V	230	50÷60	-15.. +35	Te	140	76	34	50 RQ5768/B ●
DUELUCI TD/PS P	35÷50W 12V + 100÷500W 230V	230	50÷60	-15.. +35	Te	140	76	34	50 RQ5769/B ●



12V + 230V + 2 POT. SEP.

Article Artikel	W min. max.	V	Hz	ta °C	W	L mm	P mm	H mm	Code Art.-Nr.
2BT/PS N	20÷60W 12V + 20÷60W 230V	230	50÷60	-15.. +35	Te	140	76	34	50 RQ5790 ●
2BT/PS P	20÷60W 12V + 20÷60W 230V	230	50÷60	-15.. +35	Te	140	76	34	50 RQ5794 ●



12V + 230V + 2 POT. SEP. 

Article Artikel	W min. max.	V	Hz	ta °C	W	L mm	P mm	H mm	Code Art.-Nr.
DUELUCI TD/PC N	35÷50W 12V + 75÷300W 230V	230	50÷60	-15.. +35	P	140	76	34	50 RQ0505 ●